

Matomo是一个开源的网站分析平台

<https://matomo.org>

下载，将 zip 文件解压缩到硬盘驱动器上的文件夹中。这将创建一个包含文件和目录的“matomo”文件夹。

```
wget https://builds.matomo.org/matomo.zip
unzip matomo.zip
mv ./matomo /var/www/
chown -R www-data:www-data /var/www/matomo
```

配置依赖

```
apt install php php-curl php-gd php-cli mysql-server php-mysql php-xml php-mbstring
```

数据库设置

```
#连接到您的 MySQL 数据库
mysql -u root -p
输入密码,后enter
#为 Matomo 创建数据库:
CREATE DATABASE matomo_db;
#显示数据库
SHOW DATABASES;
#权限
#创建其他用户
CREATE USER admin IDENTIFIED BY "*****";
#WordPress权限授权给admin用户
GRANT ALL PRIVILEGES ON matomo_db.* TO admin;
#系统会重新加载权限表，确保使用的是最新的权限设置。
FLUSH PRIVILEGES;
#退出mysql数据库
EXIT;
```

服务器配置

[matomo.conf](#)

```
server {
    listen [::]:443 ssl http2; # remove this if you don't want Matomo
    to be reachable from IPv6
    listen 443 ssl http2;
    server_name matomo.localhost; # list all domains Matomo should be
    reachable from
    access_log /var/log/nginx/matomo.access.log;
    error_log /var/log/nginx/matomo.error.log;

    ## uncomment if you want to enable HSTS with 6 months cache
    ## ATTENTION: Be sure you know the implications of this change (you
    won't be able to disable HTTPS anymore)
    add_header Strict-Transport-Security max-age=15768000 always;
```

```
## replace with your SSL certificate
ssl_certificate      /etc/nginx/conf.d/cert/localhost.pem;
ssl_certificate_key  /etc/nginx/conf.d/cert/localhost.key;

# include ssl.conf; # if you want to support older browsers, please
read through this file
# ssl_session_timeout 1d;
# ssl_session_cache shared:SSL:50m;
# ssl_session_tickets off;
# modern configuration. tweak to your needs.
# ssl_protocols TLSv1.2;
# ssl_ciphers 'ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-
SHA384:ECDHE-ECDSA-CHACHA20-POLY1305:ECDHE-RSA-CHACHA20-POLY1305:ECDHE-
ECDSA-AES128-GCM-SHA256:ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES256-
SHA384:ECDHE-RSA-AES256-SHA384:ECDHE-ECDSA-AES128-SHA256:ECDHE-RSA-
AES128-SHA256';
# ssl_prefer_server_ciphers on;
# OCSP Stapling ---
# fetch OCSP records from URL in ssl_certificate and cache them
ssl_stapling on;
ssl_stapling_verify on;

add_header Referrer-Policy origin always; # make sure outgoing
links don't show the URL to the Matomo instance
add_header X-Content-Type-Options "nosniff" always;
add_header X-XSS-Protection "1; mode=block" always;

root /var/www/matomo/; # replace with path to your matomo instance

index index.php;

## only allow accessing the following php files
location ~
^(index|matomo|piwik|js/index|plugins/HeatmapSessionRecording/configs)
\.php$ {
    include snippets/fastcgi-php.conf; # if your Nginx setup
doesn't come with a default fastcgi-php config, you can fetch it from
https://github.com/nginx/nginx/blob/master/conf/fastcgi.conf
    try_files $fastcgi_script_name =404; # protects against
CVE-2019-11043. If this line is already included in your
snippets/fastcgi-php.conf you can comment it here.
    fastcgi_param HTTP_PROXY ""; # prohibit httpoxy:
https://httpoxy.org/
    fastcgi_pass unix:/run/php/php8.2-fpm.sock; #replace with the
path to your PHP socket file
    #fastcgi_pass 127.0.0.1:9000; # uncomment if you are using PHP
via TCP sockets (e.g. Docker container)
}

## deny access to all other .php files
```

```
location ~* ^.+\.php$ {
    deny all;
    return 403;
}

## serve all other files normally
location / {
    try_files $uri $uri/ =404;
}

## disable all access to the following directories
location ~ ^/(config|tmp|core|lang) {
    deny all;
    return 403; # replace with 404 to not show these directories
exist
}

location ~ /\.ht {
    deny all;
    return 403;
}

location ~ js/container_.*_preview\.js$ {
    expires off;
    add_header Cache-Control 'private, no-cache, no-store';
}

location ~
\.(gif|ico|jpg|png|svg|js|css|htm|html|mp3|mp4|wav|ogg|avi|ttf|eot|woff
|woff2)$ {
    allow all;
    ## Cache images,CSS,JS and webfonts for an hour
    ## Increasing the duration may improve the load-time, but may
    cause old files to show after an Matomo upgrade
    expires 1h;
    add_header Pragma public;
    add_header Cache-Control "public";
}

location ~ ^/(libs|vendor|plugins|misc|node_modules) {
    deny all;
    return 403;
}

## properly display textfiles in root directory
location ~/(.*\.md|LEGALNOTICE|LICENSE) {
    default_type text/plain;
}
}
# vim: filetype=nginx
```

添加Nginx规则

```
cd /etc/nginx/conf.d/  
#粘贴Nginx配置matomo.conf  
#查看nginx的配置文件路径, 记录nginx.conf路径  
nginx -t  
sudo systemctl restart nginx
```

浏览器访问

欢迎屏幕

是时候开始点击式安装了！单击下一步 »

安装 JavaScript 跟踪标记

在您要分析的每个页面上安装 Matomo 生成的 JavaScript 跟踪标签。建议将此代码放在结束标记之前或包含在所有页面顶部的共享头文件中</head>

```
vi /var/www/dokuwiki/lib/tpl/bootstrap3/main.php  
  
<head>...  
  
<!-- Matomo -->  
<script>  
  var _paq = window._paq = window._paq || [];  
  /* tracker methods like "setCustomDimension" should be called before  
  "trackPageView" */  
  _paq.push(['trackPageView']);  
  _paq.push(['enableLinkTracking']);  
  (function() {  
    var u="//localhost/";  
    _paq.push(['setTrackerUrl', u+'matomo.php']);  
    _paq.push(['setSiteId', '1']);  
    var d=document, g=d.createElement('script'),  
s=d.getElementsByTagName('script')[0];  
    g.async=true; g.src=u+'matomo.js'; s.parentNode.insertBefore(g,s);  
  })();  
</script>  
<!-- End Matomo Code -->  
  
</head>
```

From:

<https://sujj.wiki/> - 落月思君归

Permanent link:

<https://sujj.wiki/doku.php?id=%E8%BD%AF%E4%BB%B6:matomo&rev=1759762897>

Last update: **2026/01/02 02:08**

