

OnlyOffice

<https://www.onlyoffice.com/zh/download-community>

```
#访问
https://github.com/ONLYOFFICE/DocumentServer/releases
#下载ONLYOFFICE-DocumentServer-9.2.0
wget
https://github.com/ONLYOFFICE/DocumentServer/releases/download/v9.2.0/onlyoffice-documentserver_amd64.deb
scp .\onlyoffice-documentserver_amd64.deb user@example.com:/home/user
sha256sum onlyoffice-documentserver_amd64.deb
sha256:2a42e5c47080650a70d2d5e7f9df9c126a37bbd5786e3bffb8adb88e8a01843e

sudo apt install postgresql libstdc++6 nginx
sudo apt install redis-server
sudo apt install rabbitmq-server
sudo apt install nginx-extras

#/etc/apt/sources.list 添加 contrib non-free
#默认注释了源码镜像以提高 apt update 速度，如有需要可自行取消注释
deb https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie main contrib non-free non-free-firmware
# deb-src https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie main contrib non-free non-free-firmware
deb https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie-updates main contrib non-free non-free-firmware
# deb-src https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie-updates main contrib non-free non-free-firmware
deb https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie-backports main contrib non-free non-free-firmware
# deb-src https://mirrors.tuna.tsinghua.edu.cn/debian/ trixie-backports main contrib non-free non-free-firmware
#以下安全更新软件源包含了官方源与镜像站配置，如有需要可自行修改注释切换
deb https://security.debian.org/debian-security trixie-security main contrib non-free non-free-firmware
# deb-src https://security.debian.org/debian-security trixie-security main contrib non-free non-free-firmware
sudo apt install ttf-mscorefonts-installer

sudo -i -u postgres psql -c "CREATE USER onlyoffice WITH PASSWORD 'onlyoffice';"
sudo -i -u postgres psql -c "CREATE DATABASE onlyoffice OWNER onlyoffice;"
sudo -i -u postgres psql -c "ALTER ROLE onlyoffice WITH LOGIN CREATEDB;"

sudo apt install ./onlyoffice-documentserver_amd64.deb
软件包设置Database Password:输入数据库密码 *****

sudo systemctl start ds-*
```

```
http://example.com/welcome/  
sudo systemctl start ds-example  
sudo systemctl enable ds-example  
http://example.com/example/  
sudo systemctl start ds-adminpanel  
sudo systemctl enable ds-adminpanel  
http://example.com/admin/
```

```
sudo vi /etc/onlyoffice/documentserver/local.json  
services.CoAuthoring.secret.browser.string  
sudo cat /var/log/onlyoffice/documentserver/adminpanel/out.log  
AdminPanel SETUP REQUIRED | Bootstrap code: *****
```

```
#修改端口 <PORT_NUMBER>=80  
echo onlyoffice-documentserver onlyoffice/ds-port select <PORT_NUMBER> |  
sudo debconf-set-selections  
echo onlyoffice-documentserver onlyoffice/db-host string <DB_HOST> | sudo  
debconf-set-selections  
echo onlyoffice-documentserver onlyoffice/db-user string <DB_USER> | sudo  
debconf-set-selections  
echo onlyoffice-documentserver onlyoffice/db-pwd password <DB_PASSWORD> |  
debconf-set-selections  
echo onlyoffice-documentserver onlyoffice/db-name string <DB_NAME> | sudo  
debconf-set-selections  
systemctl restart ds-*
```

From:

<https://sujj.wiki/> - 落月思君归

Permanent link:

<https://sujj.wiki/doku.php?id=%E8%BD%AF%E4%BB%B6:onlyoffice&rev=1766213961>

Last update: **2026/01/02 02:07**

